



Version 02/ 26.08.2010
Supercedes Version1/ 09.12.2008

The scrim reinforcement adds good dimensional stability to this highly aggressive adhesive, without losing any of the products conformability. It is therefore, a perfect solution for laminating, fixing and mounting of structured, rough surfaced substrates, where dimensional stability is required to eliminate stretching during final application.

	steel	aluminium	glass	PMMA	PVC	PP	PE
N / 25mm	15	20	25	30	35		

20° C | 10 | ---- | ---- |

N / 625mm² 0 5 10

01 / LINER
PE- paper, white,
both sides silicone coated,
weight: 120 g/m²

02 / ADHESIVE
modified adhesive based on acrylate
coating weight: 150 g/m²

03 / CARRIER
Polyesterscrim, white

The service temperature ranges from
- 40°C to +95°C, short term even up to +120°C

This product should be stored at ambient temperatures of around 20°C, avoiding wide temperature fluctuations and direct sunlight. The storage environment should have a relative humidity of approx. 50%. In ideal storage conditions, the shelf life of this material will be approx. 12 months from the delivery date. Within this 12 month period, when stored correctly, there should be no deterioration of the products published performance specification.

All statements, technical info contained herein are based on lab testing, we believe to be reliable. In reality, many factors beyond our control can affect and influence the use and performance of our products in any particular application. Since these factors are uniquely within the users knowledge and control, it is essential that the user evaluate the product to determine its suitability for purpose. BIOLINK will not be liable for any loss or damage arising, whether direct or indirect, special, incidental or consequential.

All data above mentioned and technical information given above are typical values, gained from tests we believe to be reliable. Please ensure before using our product that it is suitable for the material for intended application. For technical assistance please call our product specialists. The data and statements are intended as a source of information, are given without guarantee and do not constitute a warranty. They can vary according to the application conditions. All materials described herein are subject to our conditions of sale, a copy is available on request.



BIOLINK
tapesolutions

Biolink, Gesellschaft für Verbindungstechnologien mbH
Brunnerweg 38 · 83666 Waakirchen, Telefon +49 (0) 8021 50429-0 · Telefax +49 (0) 8021 50429-29
www.biolink-tapes.com · info@biolink-tapes.com