

FoamLink 3004 H+ is a foamtape with a very soft foam as carrier based on Polyolefine.

The special foam makes the tape very soft, flexible and very compressible by low pressure.

Foamlink 3004 H+ has a good resistance to all environmental influences, ageing and UV.


ADHESION

in accordance to AFERA 4001

* foam fracture

Steel *

N / 25mm



COHESION

in accordance to AFERA 4012

20° C

70° C

N / 625mm²



TAPECONSTRUCTION

01

02

03

04

Thickness
of tape
without liner
approx. 3.1 mm



01 / LINER

Si-paper, yellow,
both side siliconized, 92g/m²

02 / ADHESIVE

High performance adhesive based
on tackified polyacrylat
coating weight: 70 g/m²

03 / CARRIER

PE-foam, black
Thickness: 3,0 mm

04 / ADHESIVE

High performance adhesive based
on tackified polyacrylat
coating weight: 70 g/m²

The service temperature ranges from
- 40°C to +70 °C, short term even up to +90 °C

STORAGE

This product should be stored at ambient temperatures of around 20 °C, avoiding wide temperature fluctuations and direct sunlight. The storage environment should have a relative humidity of approx. 50%. In ideal storage conditions, the shelf life of this material will be approx. 12 months from the delivery date. Within this 12 month period, when stored correctly, there should be no deterioration of the products published performance specification.

All data above mentioned and technical information given above are typical values, gained from tests we believe to be reliable. Please ensure before using our product that it is suitable for the material for intended application. For technical assistance please call our product specialists. The data and statements are intended as a source of information, are given without guarantee and do not constitute a warranty. They can vary according to the application conditions. All materials described herein are subject to our conditions of sale, a copy is available on request.