



UniLINK 110 H+ is a double coated adhesive tape for all fixing and mounting applications with a carrier for dimensional stability.

ADHESION

in accordance to AFERA 4001

Afera steel	25	-----	-----	-----	-----	
aluminium	23	----	----	----	----	----
glass	24	----	----	----	----	----
Plexiglas	23	----	----	----	----	----
PVC	22	----	----	----	----	----
PP	20	----	----	----	----	----
PE	11	----	----	----	----	----
N / 25mm		5	10	15	20	25

COHESION

in accordance to AFERA 4012

20° C	45	-----	-----	-----	-----	-----	-----	-----	-----
70° C	10	----	----	----	----	----	----	----	----
N / 625mm ²		0	10	20	30	40			

TAPECONSTRUCTION

01
02
03
04

Thickness
of tape
without liner
approx. 013 mm



01 / LINER

PE- coated paper, white,
both sides siliconized, 120 g/m

02 / ADHESIVE

High performance adhesive based
on polyacrylate
Film thickness: 65 g/m²

03 / CARRIER

specialpaper
substance: 12g/m²

04 / ADHESIVE

High performance adhesive based
on polyacrylate
Film thickness: 65 g/m²

The service temperature ranges from
- 40°C to +120°C, short term even up to +150°C

STORAGE

This product should be stored at ambient temperatures of around 20° C, avoiding wide temperature fluctuations and direct sunlight. The storage environment should have a relative humidity of approx. 50%. In ideal storage conditions, the shelf life of this material will be approx. 12 months from the delivery date. Within this 12 month period, when stored correctly, there should be no deterioration of the products published performance specification.

All data above mentioned and technical information given above are typical values, gained from tests we believe to be reliable. Please ensure before using our product that it is suitable for the material for intended application. For technical assistance please call our product specialists. The data and statements are intended as a source of information, are given without guarantee and do not constitute a warranty. They can vary according to the application conditions. All materials described herein are subject to our conditions of sale, a copy is available on request.